



DG112 Digital CO₂/O₂ Probe

The challenge of measuring gas concentrations within incubators is indeed complex, particularly due to the potential for disturbance to the incubator's environment caused by gas aspiration. The precision of gas measurement is crucial in applications such as cell culture, where maintaining an environment that closely mimics in vivo conditions is essential for cell growth and reproduction.

Functions & Technology

CO_2/O_2 probe

The Digital Carbon Dioxide (CO_2) and Oxygen (O_2) probe represents a significant advancement in incubator control technology. Its innovative flat design make it an ideal choice for a variety of laboratory settings, including desktop incubators. This probe enables continuous monitoring of CO_2 and O_2 levels, which is crucial for maintaining the optimal environment for cell cultures and other sensitive biological samples.





Specifications

Sensors Measure range Accuracy T90 Compensation for ambient conditions Display resolution and update Cable length Compliances Calibration NDIR (CO₂), Electro-chemical (O₂) $0 - 30\% O_2/0 - 12\% CO_2$ $0,2\% O_2, 0,1\% CO_2 \pm 3\%$ of reading < 20 sec. (O₂), < 15 sec. (CO₂) Temperature (20 - 40 °C), altitude (700 - 1100 mbar) 0,1%, one update per sec. 2 mCE with NiloChecker 500 • RoHs Delivered with factory calibration certificate Can be calibrated in accordance with ISO/IEC 17025. 0 - 50 °C Calibration requires adaptor. Part no: 115s001 5 - 95% RH (Non condensing)



Operating conditions

Ordering info

 Part no: 112s003 - DG112 VFC (Very flat cable for desktop incubators)

 Delivered with Factory calibration certificate.

 Part no: 800s015 - Calibration of Nilotech gasprobe incl. factory and gas certificates





Knudstrupvej 14 - DK-4270 Hoeng, Denmark

+45 30 32 32 96 - contact@nilotech.eu - www.nilotech.eu